

## Model 1100 3-Point Anhydrous Toolbar Specifications

|   |   |
|---|---|
| Working Widths                                      | 15', 20', 24', 27-1/2', 30', 32-1/2', & 37-1/2'   |
| Mainframe & Wing Tubing                             | 7" x 5" Rectangular Tubing  |
| Toolbar Rank  | 30"   |
| 3-Point Hitch                                       | Category II & III   |
| Transport Width w/o Inline Transport                | 15' & 20' Rigid Frame (does not fold)<br>24, 27-1/2', 30', 32-1/2' width is 15-1/2'<br>37-1/2' width is 21'             |
| Transport Width w/Inline Transport                  | All Sizes - 10'   |
| Transport Height                                    | 24' - 9', 27-1/2' & 30' - 11', 32-1/2' & 37-1/2' - 13'<br>*Must add lift height when transporting on 3-point of tractor |
| Transport Height w/Inline Transport                 | All Sizes - 5'  |
| Pin-Adjust Gauge/Transport Wheels                   | 9.5 x 15  |
| Rear Hitch Assembly                                 | Rigid with Telescoping Drawbar  |
| Safety Lighting System                              | Standard Equipment  |
| Inline Transport                                    | Optional  |
| Rigid Shank Mounts w/20" Spring Loaded Coulter      | Optional  |
| Auto-Reset Shank Mounts w/20" Spring Loaded Coulter | Optional  |
| 18" Trash Titan Disk Sealer                         | Optional  |
| Water Rinse Tank w/Toolbox                          | Optional  |
| Monitor Mounting Bracket (Raven/Hinicker)           | Optional  |

**Progressive Farm Products, Inc.**  
**19500 N 1425 East Road**  
**Hudson, IL 61748**  
**(309) 454-1564**

Specifications subject to change without notice or obligation.