

MODEL 2450 SIDEDRESS APPLICATOR SPECIFICATIONS

Available sizes (working width)	37 1/2'
Mainframe & Wing Tubing	7" x 7" x 3/8" square tubing
Front Hitch	7" x 7" x 3/8" square tubing
Transport Width	16 1/2'
Transport Height	12' 6"
18.4 x 26 - 10 ply Mainframe Wheels	Optional
13.6 x 38 - 12 ply Mainframe Wheels	Optional
Standard Tank Capacity	1000 gallon
Coulter Assembly - 1200# Trip Pressure	20" swivel with 32" crop clearance
12 to 16 Row Quick Change	Standard Equipment
Patented Midmount Design	Standard Equipment
Safety Lighting System	Standard Equipment
Combo Hitch Clevis (single/double)	Standard Equipment
Adjustable Axle	Standard Equipment
No Drip Manifold System	Standard Equipment
2" Rear Quick Fill	Standard Equipment
Ground Drive Pump System	John Blue Single or Double Piston Pump
Hydraulic Pump w/Teejet Metering System	Optional - in lieu of ground drive pump system
Knife Kit	Optional
Liquid Injection Kit	Optional
Water Rinse Tank w/toolbox	Optional

Progressive Farm Products, Inc.
19500 N. 1425 East Road
Hudson, IL 61748
(309) 454-1564

Specifications subject to change without notice or obligation.